NSN 5950-01-100-5863

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-100-5863
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.937 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.937 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and brought out to terminal single component
Body Length:
1.450 inches
Body Width:
1.450 inches
Body Height:
1.780 inches
Maximum Operating Temp:
71.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Thread Size:
0.164 inches single group
Winding Operating Current:
63.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
8.00 ac volts single component 1st secondary and 40.00 ac volts single component 1st secondary and 48.00 ac volts single component 1st
secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
14 turret
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-01-100-5863

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0