

View Online at <https://aerobasegroup.com/nsn/5950-01-100-5863>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.937 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.937 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

1.450 inches

Body Width:

1.450 inches

Body Height:

1.780 inches

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

63.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

8.00 ac volts single component 1st secondary and 40.00 ac volts single component 1st secondary and 48.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0