

View Online at <https://aerobasegroup.com/nsn/5950-01-100-5864>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.625 inches

Body Width:

2.500 inches

Body Height:

2.186 inches

Maximum Operating Temp:

110.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.5 amperes ac single component 3rd secondary and 2.5 amperes ac single component 3rd secondary

Winding Operating Voltage:

8.13 dc volts single component 3rd secondary and 8.55 dc volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0