

View Online at <https://aerobasegroup.com/nsn/5950-01-101-7885>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.484 inches single mounting facility single center group and 4.516 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.484 inches single mounting facility single center group and 3.516 inches single mounting facility single center group

Frequency Rating:

5.0 kilohertz single component and 6.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 5.940 inches and 6.060 inches

Body Width:

Between 4.940 inches and 5.060 inches

Body Height:

Between 5.810 inches and 6.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

11.0 amperes ac single component single secondary

Winding Operating Voltage:

54.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0