NSN 5950-01-103-4845

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-103-4845

| 9 april 10 a |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.750 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.180 inches single group |
| Frequency Rating: |
| 47.0 hertz single component and 63.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 3.560 inches |
| Body Width: |
| 3.880 inches |
| Body Height: |
| 4.250 inches |
| Maximum Operating Temp: |
| 75.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Operating Voltage: |
| 105.00 ac volts single component single primary and 132.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 7 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A058b0