

View Online at <https://aerobasegroup.com/nsn/5950-01-103-8906>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.196 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.875 inches

Body Width:

3.250 inches

Body Height:

3.594 inches

Distance Between Mounting Facility Centers:

1.687 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

6.0 milliamperes ac single component 1st secondary and 756.0 milliamperes ac single component 1st secondary

Winding Power Rating:

49.1 volts-amperes single component 1st secondary

Winding Operating Voltage:

22.95 ac volts single component 1st secondary and 42.05 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0