NSN 5950-01-104-3438

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-104-3438

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.690 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.031 inches single mounting facility single center group

Mounting Hole Diameter:

0.157 inches single group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.312 inches

Body Width:

2.125 inches

Body Height:

2.312 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

600.0 milliamperes ac single component single primary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

81349-mil-t-27/158 government specification

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-01-104-3438

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0