
NSN 5950-01-104-4450

Reactor - Page 1 of 1



Reliability Indicator:

Not established

Inductance Type:

Fixed

Inductance Rating:

25.00 millihenries single component single winding

Frequency Rating:

15.0 kilohertz single component

Body Length:

0.240 inches

Body Outside Diameter:

0.360 inches

Maximum Operating Temp:

105.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

13.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

38.000 single component single winding

Test Data Document:

81349-mil-prf-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 wire lead

Specification Data:

81349 - mil-prf-27/146 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

Mil-std (military Standard):

Mil-prf-27 spec.

