NSN 5950-01-104-7110

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-104-7110

view Offiline at https://aerobasegroup.com/nsi//0900-01-104-7110
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
1.156 inches
Overall Width:
0.813 inches
Inductance Type:
Mechanically adjustable
Inductance Rating:
1.10 henry single component single winding and 11.00 henry single component single winding
Frequency Rating:
60.0 hertz single component
Body Height:
Between 1.111 inches and 1.171 inches
Maximum Operating Temp:
105.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thread Size:
0.112 inches single group
Winding Operating Current:
7.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
360.000 single component single winding
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single group
Terminal Type And Quantity:

81349-mil-t-27/145 government specification

2 tab, solder lug

Specification Data:

NSN 5950-01-104-7110

Reactor - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0