NSN 5950-01-105-1220

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-105-1220 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.185 inches single group |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length: |
| 4.600 inches |
| Body Width: |
| 2.950 inches |
| Body Height: |
| 3.570 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Slot single group |
| Winding Function And Quantity: |
| 2 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 6.0 amperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 87.00 ac volts single component 1st secondary |
| Terminal Type And Quantity: |
| 11 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A058b0