

View Online at <https://aerobasegroup.com/nsn/5950-01-105-1224>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant and vibration resistant

**Overall Length:**

3.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.428 inches single mounting facility single center group and 2.448 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.990 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

**Overall Height:**

2.700 inches

**Overall Width:**

1.875 inches

**Mounting Hole Diameter:**

0.151 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-wye

**Maximum Transformer Power Rating:**

25.0 watts single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Maximum Operating Temp:**

100.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Winding Operating Current:**

5.5 amperes dc single component 2nd secondary

**Winding Operating Voltage:**

22.40 ac volts single component 2nd secondary

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0