

View Online at <https://aerobasegroup.com/nsn/5950-01-105-1224>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration resistant

Overall Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.428 inches single mounting facility single center group and 2.448 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.990 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

Overall Height:

2.700 inches

Overall Width:

1.875 inches

Mounting Hole Diameter:

0.151 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Maximum Transformer Power Rating:

25.0 watts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

5.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

22.40 ac volts single component 2nd secondary

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0