

View Online at <https://aerobasegroup.com/nsn/5950-01-105-1617>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Mounting Slot Width:

0.219 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.688 inches

Body Width:

4.938 inches

Body Height:

4.188 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

4.35 amperes ac single component single secondary

Winding Power Rating:

500.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

220.00 ac volts single component all primary and 240.00 ac volts single component all primary

Special Features:

Terminal output side of transformer have 3 screw terminals for mounting a fuse kit if needed

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0