NSN 5950-01-105-1617

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-105-1617
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.062 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.750 inches single mounting facility single center group
Mounting Slot Width:
0.219 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
6.688 inches
Body Width:
4.938 inches
Body Height:
4.188 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Bracket single group and slot single group
Winding Function And Quantity:
2 primary single component and 1 secondary single component
Winding Operating Current:
4.35 amperes ac single component single secondary
Winding Power Rating:
500.0 volts-amperes single component 1st secondary
Winding Operating Voltage:
$220.00\ \text{ac}\ \text{volts}\ \ \text{single}\ \text{component}\ \text{all}\ \text{primary}$ and $240.00\ \text{ac}\ \text{volts}\ \ \text{single}\ \text{component}\ \text{all}\ \text{primary}$
Special Features:
Terminal output side of transformer have 3 screw terminals for mounting a fuse kit if needed
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

No

NSN 5950-01-105-1617

Power Transformer - Page 2 of 2



Fiig:

A058b0