NSN 5950-01-105-1970

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-105-1970

| Reliability Indicator: |
|---|
| Not established |
| |
| Turn Quantity: |
| 73 single component single winding |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 200.00 microhenries single component single winding and 300.00 microhenries single component single winding |
| Frequency Rating: |
| 10.0 kilohertz single component |
| Body Length: |
| 1.100 inches |
| Body Outside Diameter: |
| 1.500 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 1 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding and winding turns single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Conductor Size: |
| 0.04030 inches american wire gage single component single winding |
| Winding Operating Current: |
| 4.0 amperes dc single component single winding and 6.5 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.080 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 2 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-01-105-1970

Reactor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A058b0