

View Online at <https://aerobasegroup.com/nsn/5950-01-105-4785>

Reliability Indicator:

Not established

Overall Length:

6.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility single center group

Overall Height:

5.500 inches

Overall Width:

3.750 inches

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Winding Operating Current:

3.8 amperes ac single component 4th secondary

Winding Operating Voltage:

105.00 ac volts single component all primary and 110.00 ac volts single component all primary and 115.00 ac volts single component all primary

Terminal Type And Quantity:

19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0