

View Online at <https://aerobasegroup.com/nsn/5950-01-105-8155>

Reliability Indicator:

Not established

Overall Length:

Between 2.210 inches and 2.290 inches

Overall Height:

1.530 inches

Overall Width:

Between 1.840 inches and 1.920 inches

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded and brought out to primary terminal single component

Distance Between Mounting Facility Centers:

1.085 inches single mounting facility single center group and 1.515 inches single mounting facility single center group

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

180.0 milliamperes ac single component single secondary

Winding Power Rating:

6.08 volts-amperes single component single secondary

Winding Operating Voltage:

33.50 ac pounds per hour wet single component single secondary 105.00 ac pounds per hour dry single component all primary and 130.00 ac pounds per hour with retaining chain single component all primary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0