

View Online at <https://aerobasegroup.com/nsn/5950-01-107-6087>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant and corrosion resistant

Overall Length:

13.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.844 inches single mounting facility single center group

Overall Height:

9.250 inches

Overall Width:

8.680 inches

Mounting Hole Diameter:

0.312 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Maximum Operating Temp:

60.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

W/overload protection

Winding Operating Current:

12.0 amperes ac single component single secondary

Winding Operating Voltage:

300.00 ac volts single component single secondary and 330.00 ac volts single component single secondary and 360.00 ac volts single component single secondary

Terminal Type And Quantity:

3 bus (bar) conductor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0