

View Online at <https://aerobasegroup.com/nsn/5950-01-107-9830>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.938 inches

Body Width:

3.375 inches

Body Height:

5.250 inches

End Application:

Tarawa class lha, low pressure (lp) dry air-dehydrators, spruance class dd (963), usns henry j. Kaiser class tao, I.P. Compressors, wasp class lhd, ticonderoga class cg (47), air compressors, high pressure

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

460.00 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0