

View Online at <https://aerobasegroup.com/nsn/5950-01-107-9830>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.438 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

3.938 inches

**Body Width:**

3.375 inches

**Body Height:**

5.250 inches

**End Application:**

Tarawa class lha, low pressure (lp) dry air-dehydrators, spruance class dd (963), usns henry j. Kaiser class tao, I.P. Compressors, wasp class lhd, ticonderoga class cg (47), air compressors, high pressure

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

1.0 amperes ac single component single secondary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

460.00 ac volts single component single primary

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

4 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0