## NSN 5950-01-108-2450

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-108-2450

Reliability Indicator:
Not established
Overall Length:
4.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches single mounting facility single center group
Overall Width:
3.810 inches
Frequency Rating:
50.0 hertz single component and 400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
5.750 inches
Body Width:
4.600 inches
Body Height:
5.750 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Terminal single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Features Provided:
Color coded lead and tinned wire leads
Winding Operating Current:
300.0 milliamperes ac single component all secondary
Winding Operating Voltage:
100.00 ac volts single component single primary and 120.00 ac volts single component single primary
Special Features:
Terminals three, four, and five are split for multiple connections
Terminal Type And Quantity:
3 wire lead and 13 wire lead w/lug
Shelf Life:

N/a

## NSN 5950-01-108-2450

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0