## NSN 5950-01-108-3100

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-108-3100

Reliability Indicator:							
Not established							
Center To Center Distance Between Mounting Facilities Parallel To Length:							
3.000 inches single mounting facility single center group							
Center To Center Distance Between Mounting Facilities Parallel To Width:							
2.438 inches single mounting facility single center group							
Frequency Rating:							
57.0 hertz single component and 440.0 hertz single component							
Input-output Phase Relationship:							
Single phase to single phase single component							
Winding Shielding Method:							
Internal shield grounded to inclosure single component							
Body Length:							
3.938 inches							
Body Width:							
2.438 inches							
Body Height:							
5.250 inches							
Maximum Operating Temp:							
105.0 degrees celsius							
Inclosure Type:							
Fully enclosed							
Mounting Facility Quantity:							
4 single group							
Mounting Method:							
Threaded stud single group							
Winding Function And Quantity:							
1 primary single component and 4 secondary single component							
Thready Qty Per Inch (tpi):							
32 single group							
Thread Size:							
0.190 inches single group							
Winding Operating Current:							
3.0 amperes dc single component 3rd secondary							
Winding Operating Voltage:							
101.00 ac volts single component single primary and 108.00 ac volts single component single primary and 115.00 ac volts single							

Unf single group

**Terminal Type And Quantity:** 

**Thread Series Designator:** 

component single primary and 122.00 ac volts single component single primary

14 pin

Shelf Life:

N/a

## NSN 5950-01-108-3100

Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A058b0