

View Online at <https://aerobasegroup.com/nsn/5950-01-108-3100>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.938 inches

Body Width:

2.438 inches

Body Height:

5.250 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes dc single component 3rd secondary

Winding Operating Voltage:

101.00 ac volts single component single primary and 108.00 ac volts single component single primary and 115.00 ac volts single component single primary and 122.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0