

View Online at <https://aerobasegroup.com/nsn/5950-01-108-8208>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

14.0 kilohertz single component and 60.0 kilohertz single component

Maximum Transformer Power Rating:

3.0 watts single component

Primary To Secondary Turn Ratio:

8 to 1 single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.660 inches

Body Width:

1.300 inches

Body Height:

2.660 inches

Maximum Operating Temp:

75.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0