

View Online at <https://aerobasegroup.com/nsn/5950-01-108-8270>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Overall Height:

3.250 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.938 inches

Body Width:

1.812 inches

Body Height:

2.750 inches

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

25.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

6.75 ac volts single component 2nd primary and 8.00 ac volts single component 2nd primary and 13.50 ac volts single component 2nd primary and 14.75 ac volts single component 2nd primary and 21.50 ac volts single component 2nd primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0