

View Online at <https://aerobasegroup.com/nsn/5950-01-108-8554>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.171 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.500 inches

Body Width:

2.000 inches

Body Height:

1.688 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Voltage:

8.90 ac pounds per hour wet single component 2nd secondary and 34.50 ac pounds per hour wet single component 2nd secondary and

43.40 ac pounds per hour wet single component 2nd secondary

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0