NSN 5950-01-109-7159

Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-109-7159

Not established Impedance Rating In Ohms: 100.0 single component single primary and 1200.0 single component single primary Frequency Rating: 300.0 hertz single component and 20.0 kilohertz single component Maximum Transformer Power Rating: 100.0 miliwatts single component Baddy Length: 0.469 inchas Body Length: 0.489 inchas Body Outside Diameter: 0.344 inchas Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: 1 creminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Function (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 181349-mil-t-27/172 government specification Sheft Life: No Dimilitarization: No Filig:	
Impedance Rating In Ohms: 1000.0 single component single primary and 1200.0 single component single primary Frequency Rating: 300.0 hertz single component and 20.0 kilohertz single component Maximum Transformer Power Rating: 100.0 milliwalts single component Body Length: 0.489 inches Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes de single component single primary Test Data Document: 81349-mil-1-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-27/172 government specification Shelf Life: Na Unit Of Measure: — Demilitarization: No Flig:	Reliability Indicator:
1000.0 single component single primary and 1200.0 single component single primary Frequency Rating: 300.0 hertz single component and 20.0 kilohertz single component Maximum Transformer Power Rating: 100.0 milliwatts single component Body Length: 0.469 inches Body Outside Diameter: 0.480 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes de single component single primary Test Data Document: 81349-mill-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-milt-27/172 government specification Sheff Life: N/a Unit Of Measure: — Demilitarization: No Flig:	
Frequency Rating: 300.0 hetz single component and 20.0 kilohertz single component Maximum Transformer Power Rating: 100.0 millivants single component Body Length: 0.469 inches Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes de single component single primary Test Data Document: 3.1349-mill-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mill-t-27/172 government specification Shelf Life: Na Unit Of Measure: - Demilitarization: No Filig:	
Maximum Transformer Power Rating: 10.0.0 milliwatts single component Maximum Transformer Power Rating: 10.0.0 milliwatts single component Body Length: 0.469 inches Body Outside Diameter: 0.344 inches Maximum Operating Temp: 10.5.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 8.1349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil+27/172 government specification Shelf Life: N/a Unit Of Measure:	1000.0 single component single primary and 1200.0 single component single primary
Maximum Transformer Power Rating: 100.0 milliwatts single component Body Length: 0.469 inches Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes do single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	Frequency Rating:
Body Length: 0.469 inches Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil+27172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	300.0 hertz single component and 20.0 kilohertz single component
Body Length: 0.469 inches Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Maximum Transformer Power Rating:
Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 8.1349-milt-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-milt-27/172 government specification Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	100.0 milliwatts single component
Body Outside Diameter: 0.344 inches Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes de single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: No Unit Of Measure: Demilitarization: No Fig:	Body Length:
Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes de single component single primary Test Data Document: 81349-mil-1-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-1-27/172 government specification Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	0.469 inches
Maximum Operating Temp: 105.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Outside Diameter:
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.344 inches
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Operating Temp:
Fully enclosed Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	105.0 degrees celsius
Mounting Method: Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Type:
Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Fully enclosed
Terminal single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A058b0	Mounting Method:
1 primary single component and 1 secondary single component Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal single group
Winding Operating Current: 3.0 milliamperes dc single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Winding Function And Quantity:
3.0 milliamperes do single component single primary Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	1 primary single component and 1 secondary single component
Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Operating Current:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.0 milliamperes dc single component single primary
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Terminal Type And Quantity: 4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
4 wire lead Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data: 81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
81349-mil-t-27/172 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4 wire lead
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-t-27/172 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A058b0	Fiig:
	A058b0