# NSN 5950-01-111-0740

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-111-0740

| Reliability | Indicator: |
|-------------|------------|
|-------------|------------|

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.875 inches single mounting facility single center group

#### **Mounting Hole Diameter:**

0.188 inches single group

#### Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Maximum Transformer Power Rating:**

1000.0 watts single component

# Winding Shielding Method:

Internal shield grounded to core single component

**Body Length:** 

4.500 inches

**Body Width:** 

7.875 inches

# **Body Height:**

5.313 inches

#### **Inclosure Type:**

Partially enclosed, double shell

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Bracket single group and unthreaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

# **Winding Operating Current:**

1.7 amperes ac single component single primary

### **Winding Operating Voltage:**

115.00 ac volts single component single secondary

### **Terminal Type And Quantity:**

4 wire lead

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

# Demilitarization:

No

# NSN 5950-01-111-0740

Power Transformer - Page 2 of 2



Fiig:

A058b0