

View Online at <https://aerobasegroup.com/nsn/5950-01-111-0964>

Reliability Indicator:

Not established

Mounting Hole Diameter:

1.500 inches single group

Inductance Rating:

55.00 microhenries single component all winding

Core Construction:

S0lid single component

Body Length:

3.870 inches

Body Outside Diameter:

4.250 inches

End Application:

Ticonderoga class cg (47), nimitz class cvn, arleigh burke class ddg, oliver perry class ffg, spruance class dd (963), supply class aoe, computer display set, an/uyq-21 (v), wasp class lhd, sonar signal processing sys, an/sqq-28 (v), forrestal class cv

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component all winding

Winding Operating Current:

6.0 amperes dc single component all winding

Dc Resistance Rating In Ohms:

0.180 single component all winding

Criticality Code Justification:

Feat

Winding Operating Voltage:

100.00 ac pounds per hour wet single component all winding

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0