

View Online at <https://aerobasegroup.com/nsn/5950-01-113-5068>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

5.562 inches

Body Width:

4.312 inches

Body Height:

3.688 inches

Maximum Operating Temp:

85.0 degrees celsius

Distance Between Mounting Facility Centers:

2.750 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 1st group

Mounting Method:

Threaded stud 2nd group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 2nd group

Thread Size:

0.190 inches 1st group

Winding Operating Current:

13.0 amperes dc single component single secondary

Winding Operating Voltage:

115.00 ac volts single component all primary

Thread Series Designator:

Unf 1st group

Terminal Type And Quantity:

7 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0