

View Online at <https://aerobasegroup.com/nsn/5950-01-114-7077>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.196 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.880 inches

Body Width:

2.500 inches

Body Height:

4.000 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.4 amperes ac single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single primary and 115.00 ac volts single component single primary and 120.00 ac volts single component single primary and 130.00 ac volts single component single primary and 140.00 ac volts single component single primary and 150.00 ac volts single component single primary and 160.00 ac volts single component single primary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0