NSN 5950-01-114-9884

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-114-9884

Overall Length: 3.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.438 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Overall Width: 2.700 inches Mounting Hole Diameter: 0.156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Winding Shielding Method: Unthreaded hole single group Winding Shielding Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil+27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 15 fab, solder lug Shelf Life: Na Unit of Measure:	
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.438 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Overall Width: 2.700 inches Mounting Hole Diameter: 2.105 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosur Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Winding Survivor And Quantity: 5 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: Na Unit of Measure: ————————————————————————————————————	-
2.438 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Overall Width: 2.700 inches Mounting Hole Diameter: 0.156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: ————————————————————————————————————	
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches single mounting facility single center group Overall Width: 2.700 inches Mounting Hole Diameter: 0.156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-milt-27 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: Na Unit Of Measure: — Demilitarization: No Fig:	
2.000 inches single mounting facility single center group Overall Width: 2.700 inches Mounting Hole Diameter: 0.156 inches single group Winding Shleiding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Overall Width: 2,700 inches Mounting Hole Diameter: 0,156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 4 secondary single component Tost Data Document: 81349-mill-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure:	
2.700 inches Mounting Hole Diameter: 0.156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Mounting Hole Diameter: 0.156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-milt-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	Overall Width:
O.156 inches single group Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mill-1-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: Na Unit Of Measure: Demilitarization: No Fiig:	2.700 inches
Winding Shielding Method: Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Hole Diameter:
Core grounded single component Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.156 inches single group
Maximum Operating Temp: 130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Winding Shielding Method:
130.0 degrees celsius Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Core grounded single component
Inclosure Type: Open Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Operating Temp:
Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	130.0 degrees celsius
Mounting Facility Quantity: 4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Type:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Open
Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Facility Quantity:
Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	4 single group
Winding Function And Quantity: 1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Method:
1 primary single component and 4 secondary single component Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unthreaded hole single group
Test Data Document: 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Winding Function And Quantity:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 primary single component and 4 secondary single component
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Terminal Type And Quantity: 15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
15 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	15 tab, solder lug
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A058b0	Fiig:
	A058b0