## NSN 5950-01-115-1251

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-115-1251

| Reliability Indicator:   |
|--|
| Not established  |
| Turn Quantity:   |
| 31 single component single winding   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                    |
| 6.100 inches single mounting facility single center group                                    |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                     |
| 3.500 inches single mounting facility single center group                                    |
| Overall Height:  |
| 5.370 inches   |
| Mounting Slot Width:   |
| 0.300 inches single group  |
| Inductance Rating:   |
| 543.00 microhenries single component single winding  |
| Frequency Rating:  |
| 60.0 hertz single component  |
| Body Length:   |
| 7.500 inches   |
| Body Width:  |
| 4.500 inches   |
| Body Height:   |
| 3.870 inches   |
| Winding Quantity:  |
| 1 single component   |
| Inclosure Type:  |
| Open   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Slot single group  |
| Rating Method:   |
| Electrical single component single winding and winding turns single component single winding |
| Winding Conductor Size:  |
| 0.00795 inches american wire gage single component single winding                            |
| Winding Operating Current:   |
| 27.0 amperes ac single component single winding  |
| Terminal Type And Quantity:  |
| 2 wire lead w/lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

--

## NSN 5950-01-115-1251

Reactor - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A058b0