## NSN 5950-01-115-1575

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-115-1575

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.000 inches single mounting facility single center group

#### Frequency Rating:

56.0 hertz single component and 440.0 hertz single component

#### Input-output Phase Relationship:

Six phase to three phase single component

#### **Transformer Winding Connection Type:**

Wye-wye

#### **Winding Shielding Method:**

Internal shield grounded to core single component

#### **Body Length:**

**5.187** inches

#### **Body Width:**

4.730 inches

#### **Body Height:**

3.800 inches

#### **Inclosure Type:**

Open

#### **Mounting Facility Quantity:**

6 single group

#### **Mounting Method:**

Bracket single group and threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.190 inches single group

#### **Winding Operating Current:**

25.0 milliamperes dc single component 4th secondary

## **Winding Operating Voltage:**

66.40 ac volts single component single primary and 115.50 ac volts single component single primary and 132.80 ac volts single component single primary and 160.00 ac volts single component single primary

## **Thread Series Designator:**

Unf single group

## **Terminal Type And Quantity:**

1 quick disconnect, female and 1 terminal block w/screws

#### Shelf Life:

N/a

# NSN 5950-01-115-1575

Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0