

View Online at <https://aerobasegroup.com/nsn/5950-01-115-1575>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Frequency Rating:

56.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Six phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

5.187 inches

Body Width:

4.730 inches

Body Height:

3.800 inches

Inclosure Type:

Open

Mounting Facility Quantity:

6 single group

Mounting Method:

Bracket single group and threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

25.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

66.40 ac volts single component single primary and 115.50 ac volts single component single primary and 132.80 ac volts single component single primary and 160.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

1 quick disconnect, female and 1 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0