NSN 5950-01-115-2246

Power Transformer - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5950-01-115-2246

| Poliability Indicator |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches all mounting facilities 1st center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.500 inches all mounting facilities 1st center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Transformer Winding Connection Type: |
| Delta-wye |
| Body Length: |
| 5.375 inches |
| Body Width: |
| 4.600 inches |
| Body Height: |
| 4.400 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 12 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 61.4 milliamperes ac single component 1st secondary and 75.0 milliamperes dc single component 1st secondary |
| Winding Operating Voltage: |
| 7.70 dc kilovolts single component 3rd secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 12 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5950-01-115-2246

Power Transformer - Page 2 of 2



Fiig:

A058b0