NSN 5950-01-116-5043

Reactor - Page 1 of 2

Specification Data:

81349-mil-t-27/145 government specification



View Online at https://aerobasegroup.com/nsn/5950-01-116-5043

Reliability Indicator:
Not established
Inductance Type:
Mechanically adjustable
Inductance Rating:
11.00 millihenries single component single winding and 110.00 millihenries single component single winding
Frequency Rating:
1.0 kilohertz single component
Body Length:
1.156 inches
Body Width:
0.813 inches
Body Height:
1.141 inches
Distance Between Mounting Facility Centers:
0.750 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Current:
40.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
3.600 single component single winding
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
2 tab, solder lug

NSN 5950-01-116-5043

Reactor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0