NSN 5950-01-117-6082

Power Transformer - Page 1 of 1

A058b0



View Online at https://aerobasegroup.com/nsn/5950-01-117-6082

Reliability Indicator: Not established Overall Length: Between 1.345 inches and 1.405 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.925 inches single mounting facility single center group and 0.955 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter: 0.111 inches single group and 0.121 inches single group
Overall Length: Between 1.345 inches and 1.405 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.925 inches single mounting facility single center group and 0.955 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Between 1.345 inches and 1.405 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.925 inches single mounting facility single center group and 0.955 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.925 inches single mounting facility single center group and 0.955 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
0.925 inches single mounting facility single center group and 0.955 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Center To Center Distance Between Mounting Facilities Parallel To Width: 0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Overall Height: Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Between 0.865 inches and 0.895 inches Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Overall Width: Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Between 1.235 inches and 1.265 inches Mounting Hole Diameter:
Mounting Hole Diameter:
-
0.111 mores single group and 0.121 mores single group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
85.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
600.0 milliamperes ac single component single secondary
Winding Operating Voltage:
115.00 ac volts single component single primary
Terminal Type And Quantity:
5 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: