

View Online at <https://aerobasegroup.com/nsn/5950-01-117-9370>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.938 inches

Body Width:

3.375 inches

Body Height:

5.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

2.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

6.00 ac volts single component 2nd secondary and 11.00 ac volts single component 2nd secondary and 115.00 ac volts single component 2nd secondary and 120.00 ac volts single component 2nd secondary and 126.00 ac volts single component 2nd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

13 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0