

View Online at <https://aerobasegroup.com/nsn/5950-01-118-5785>

Reliability Indicator:

Not established

Overall Length:

Between 3.480 inches and 3.520 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.170 inches single mounting facility single center group and 3.190 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.920 inches single mounting facility single center group and 0.940 inches single mounting facility single center group

Overall Height:

Between 1.050 inches and 1.090 inches

Mounting Hole Diameter:

0.143 inches single group and 0.149 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Width:

Between 1.230 inches and 1.270 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

529.0 milliamperes ac single component single secondary

Winding Power Rating:

13.8 volts-amperes single component single secondary

Winding Operating Voltage:

26.00 ac volts single component single secondary

Special Features:

Secondary terminals split and brought out to two terminals each

Test Data Document:

06481-905867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0