

View Online at <https://aerobasegroup.com/nsn/5950-01-118-9723>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.512 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.200 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.188 inches

Body Width:

3.125 inches

Body Height:

3.813 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

2.5 amperes dc single component single secondary and 5.0 amperes dc single component single secondary

Winding Operating Voltage:

13.00 ac volts single component single secondary and 27.00 dc volts single component single secondary

Special Features:

Secondary volts and amps have been rectified

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0