NSN 5950-01-119-3728

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-119-3728 |
|---|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Fungus resistant and salt spray resistant and vibration resistant |
| Overall Height: |
| 0.470 inches |
| Frequency Rating: |
| 15.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Overall Diameter: |
| 0.820 inches |
| Maximum Operating Temp: |
| 110.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Winding Operating Current: |
| 70.0 milliamperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 8.50 ac volts single component 3rd secondary |
| Terminal Type And Quantity: |
| 14 pin |
| Specification Data: |
| 13973-865304 manufacturers source control |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0