

View Online at <https://aerobasegroup.com/nsn/5950-01-119-4201>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group

**Frequency Rating:**

47.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to three phase single component

**Transformer Winding Connection Type:**

Wye-wye

**Maximum Transformer Power Rating:**

200.0 volt-ampere single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

3.850 inches

**Body Width:**

3.200 inches

**Body Height:**

3.000 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 4 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

7.9 amperes dc single component 1st secondary

**Winding Operating Voltage:**

115.00 ac volts single component all primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

17 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0