

View Online at <https://aerobasegroup.com/nsn/5950-01-119-4201>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Maximum Transformer Power Rating:

200.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.850 inches

Body Width:

3.200 inches

Body Height:

3.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

7.9 amperes dc single component 1st secondary

Winding Operating Voltage:

115.00 ac volts single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0