

View Online at <https://aerobasegroup.com/nsn/5950-01-120-5098>

Reliability Indicator:

Not established

Overall Length:

Between 2.937 inches and 3.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.281 inches single mounting facility single center group and 2.297 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.843 inches single mounting facility single center group and 1.859 inches single mounting facility single center group

Overall Height:

Between 4.375 inches and 4.687 inches

Overall Width:

Between 2.500 inches and 2.625 inches

Frequency Rating:

50.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Maximum Operating Temp:

90.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

2.4 amperes ac single component all secondary

Winding Operating Voltage:

12.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0