NSN 5950-01-120-8878

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-120-8878

| g |
|--|
| Reliability Indicator: |
| Not established |
| Turn Quantity: |
| 32 single component single winding |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.187 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.437 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 400.00 microhenries single component single winding |
| Frequency Rating: |
| 2.4 kilohertz single component |
| Body Length: |
| 2.375 inches |
| Body Width: |
| 1.750 inches |
| Body Height: |
| 2.125 inches |
| Maximum Operating Temp: |
| 155.0 degrees celsius |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Bracket single group and threaded hole single group |
| Rating Method: |
| Electrical single component single winding and winding turns single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Conductor Size: |
| 0.04526 inches american wire gage single component single winding |
| Winding Operating Current: |
| 15.0 amperes dc single component single winding |

Thread Series Designator: Unc single group

NSN 5950-01-120-8878

Reactor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 2 wire hook |
| Shelf Life: |
| N/a |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0