

View Online at <https://aerobasegroup.com/nsn/5950-01-120-9202>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.430 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded and brought out to terminal single component

Body Length:

4.290 inches

Body Width:

3.530 inches

Body Height:

3.230 inches

Maximum Operating Temp:

120.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

7.5 amperes dc single component 1st secondary

Winding Operating Voltage:

100.00 ac volts single component all primary and 115.00 ac volts single component all primary and 125.00 ac volts single component all primary

Special Features:

1st secondary winding 9.5vdc and 2nd secondary winding 20.0vdc

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0