## NSN 5950-01-120-9206

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-120-9206
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
2.500 inches
Body Width:
2.500 inches
Body Height:
2.160 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Bracket single group and threaded hole single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
90.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
$99.67\ ac\ volts\ single\ component\ single\ primary\ and\ 115.00\ ac\ volts\ single\ component\ single\ primary\ and\ 130.33\ ac\ volts\ single\ component\ primary\ and\ primary\ and\ primary\ prima$
single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
12 turret
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-120-9206

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0