

View Online at <https://aerobasegroup.com/nsn/5950-01-121-7755>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.380 inches

Body Width:

1.310 inches

Body Height:

1.900 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

56 single group

Thread Size:

0.086 inches single group

Winding Operating Current:

85.0 milliamperes ac single component single secondary

Winding Operating Voltage:

9.30 ac volts single component single secondary and 9.80 ac volts single component single secondary and 10.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0