NSN 5950-01-121-9466

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-121-9466

Reliability Indicator:	Relia	ability	Indic	cator:
------------------------	-------	---------	-------	--------

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.950 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

2.812 inches

Maximum Operating Temp:

60.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

350.0 milliamperes dc single component single secondary

Winding Operating Voltage:

56.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

NSN 5950-01-121-9466

Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A058b0